



*K5R loudspeakers have been specially designed for sound systems in churches and various public buildings. These are full-range loudspeakers with exceptionally high efficiency. The K5R series of loudspeakers has been designed to provide significantly increased directivity of sound emission.*

K5R loudspeakers provide:

- aesthetic appearance
- homogeneous transmission of natural sound throughout the room
- high efficiency
- up-down handle
- version: 100V (power regulation)
- housing made of aluminum
- covered with weather-resistant paint
- colors available according to the RAL palette

Technical data		K5R-60/30		K5R-80/40		K5R-100/50		K5R-160/80		K5R-240/120
1/1 power	Impedance	60W	166Ω	80W	125Ω	100W	100Ω	160W	62,5Ω	240W
1/2 power	Impedance	30W	500Ω	40W	250Ω	50W	200Ω	80W	125Ω	120W
Input voltage		100V		100V		100V		100V		100V
Frequency response (+/-3dB) [Hz]		85 - 20000		80 - 20000		80 - 20000		75 - 20000		75 - 20000
Characteristics		omnidirectional		directional		directional		directional		directional
SPL (1W/1m) [dB]		91		94		95		97		98
SPL max. [dB]		108		113		115		119		121
Number of tweeters		1		1		1		1		2
Number of mid-woofers		1 x 5"		2 x 5"		3 x 5"		4 x 5"		6 x 5"
Dimensions height/width/depth [mm]		300/143/144		450/143/144		630/143/144		800/143/144		1200/143/144
Weight [kg]		3,8		4,3		5,2		8,5		12